


Jacket Text : CORNING FIBER 62.5/125 OPTICAL CABLE -MM/YY - OFNR (UL) c(UL) XXXXX M

# SPECIFICATION

1. Connector A ST/PC MM
2. Connector B SC/PC MM
3. Cable Type Duplex  $\phi$ 3.0mm 62.5/125um MM
4. Length XM
5. Jacket Color Orange
6. Insertion Loss <0.5 dB
7. Package Individual Bag
8. Ferrule is ceramic
9. Connector body is metal

# OPERATION :

- Fiber Extention :  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- Ferrule End-face Radius :  $10 < R < 30\text{mm}$
- Apex Offset :  $< 50\mu\text{m}$
- Increase in insertion loss after 500 mating : 0.2 dB Max.
- Operation Temperature :  $-20^\circ$  to  $+70^\circ$
- Storage Temperature :  $-40^\circ$  to  $+80^\circ$
- Humidity (non-condensing) 95%RH



	UNIT	M / M	DSGN	JOHNSON	25.SEP.2003	ITEM NO:	CP-ST/SCX
	SCALE	APPR	CHK				ST to SC Duplex Patch Cord <input type="checkbox"/> 3.0mm 62.5/125um MM
DWG NO: CP-ST-SC		<h1>CP Technologies</h1>					