



| WIRING | | |
|--------|----------------|--------|
| Plug A | Pin Assignment | Plug B |
| Pin.1 | White | Pin.1 |
| Pin.2 | Black | Pin.2 |
| Pin.3 | Red | Pin.3 |
| Pin.4 | Green | Pin.4 |
| Pin.5 | Yellow | Pin.5 |
| Pin.6 | Blue | Pin.6 |

| SPECIFICATION : UL 20251 28# 6C FLAT CABLE | | |
|--------------------------------------------|---------------|------------------------|
| ITEM | SPECIFICATION | |
| | AWG | 28AWG |
| | MATERIAL | STRANDED TINNED COPPER |
| | SIZE | 0.12mm/7 |
| INSULATION | MIN.AVG.THICK | 0.23mm |
| | MATERIAL | P.P |
| | ID. | 0.95± 0.05mm |
| NO. | 6C | |
| | | |
| BRAIN | MATERIAL | --- |
| | SIZE | --- |
| JACKET | HEIGHT | 2.5± 0.1mm |
| | WIDTH | 7.0± 0.2mm |
| | MATERIAL | PVC |
| | COLOR | SILVER |



| | | | |
|--------------|-------------------------------|---------------------|--------------|
| SCALE 1:1 | ITEM N.O.: 6c P1-P1 Tel Cable | DRAWN BY: Jane Zhaw | CUSTOMER BY: |
| | DRW DATE: 2005-8-4 | CHECKED BY: | APPROVED BY: |
| | CHANGING DATE: | APPROVED BY: | 3 R D |